


These valves, consist of a small size but high performance EH series electro-hydraulic proportional pilot relief valve and a low noise type relief valve. The valves control the system pressure proportionally through a controlled input voltage.

#### Specifications


Model Numbers	EHBG-03	EHBG-06	EHBG-10
Description			
Max. Operating Pres.	24.5 MPa (3550 PSI)		
Max. Flow	100 L/min (26.4 U.S.GPM)	200 L/min (52.8 U.S.GPM)	400 L/min (106 U.S.GPM)
Min. Flow	3 L/min (.79 U.S.GPM)	3 L/min (.79 U.S.GPM)	3 L/min (.79 U.S.GPM)
Pressure Adjustment Range	Refer to Model Number Designation		
Coil Resistance	10 Ω		
Hysteresis	Less than 2% (1%) <sup>★1</sup>		
Repeatability	Less than 1% <sup>★2</sup>		
Frequency Response	<b>C:</b> 10 (22) Hz <sup>★1</sup> <b>H:</b> 10 (25) Hz <sup>★1</sup> (-90 degree)	<b>C:</b> 7 (15) Hz <sup>★1</sup> <b>H:</b> 9.5 (18) Hz <sup>★1</sup> (-90 degree)	<b>C:</b> 7 (10.5) Hz <sup>★1</sup> <b>H:</b> 6 (14) Hz <sup>★1</sup> (-90 degree)
Supply Electric Power	24 V DC (21 to 28 V DC Included Ripple)		
Power Input (Max.)	28 W		
Input Signal	<b>C:</b> 15.7 MPa (2275 PSI) / 5 V DC <b>H:</b> 24.5 MPa (3550 PSI) / 5 V DC (At Max. Flow)		
Input Impedance	10 kΩ		
Alarm Signal Output (Open Collector)	Voltage: Max. 30 V DC Current: Max. 40 mA		
Pressure Signal Output	<b>C:</b> 5 V DC / 15.7 MPa (2275 PSI) <b>H:</b> 5 V DC / 24.5 MPa (3550 PSI)		
Ambient Temperature	0 - 50℃ (32 - 122℉) (With Circulated Air)		

★ 1. The value in ( ) is for the closed-loop type.


★ 2. The repeatability of the valve is obtained by having it tested independently on the conditions similar to its original testing.




Graphic Symbols



Open-Loop Type



Open-Loop Type with Sensor



Closed-Loop Type

#### Model Number Designation

EHB	G	-03	-C	-S	D	-50
Series Number	Type of Mounting	Valve Size	Pres. Adj. Range MPa (PSI)	Control Type	DPM	Design Number
<b>EHB:</b> Proportional Electro-Hydraulic Relief Valve	<b>G:</b> Sub-Plate Mounting	<b>03</b>	<b>C:</b> 0.6 [0.8] <sup>★</sup> - 15.7 (85 [115] - 2275) <b>H:</b> 0.6 [0.8] <sup>★</sup> - 24.5 (85 [115] - 3550)	<b>None:</b> Open-Loop	<b>None:</b> Without DPM	<b>50</b>
		<b>06</b>	<b>C:</b> 0.9 [1.0] <sup>★</sup> - 15.7 (130 [145] - 2275) <b>H:</b> 0.9 [1.0] <sup>★</sup> - 24.5 (130 [145] - 3550)	<b>S:</b> Open-Loop; with Sensor	<b>None:</b> Without DPM	<b>50</b>
		<b>10</b>	<b>C:</b> 1.1 [1.4] <sup>★</sup> - 15.7 (160 [205] - 2275) <b>H:</b> 1.1 [1.4] <sup>★</sup> - 24.5 (160 [205] - 3550)	<b>L:</b> Closed-Loop	<b>D:</b> With DPM	<b>50</b>

★ Each value of minimum adjustment pressure is of at 50% flow rate of the Max. Flow shown on the Specifications.  
The value in [ ] is for the closed-loop type.